

## **Patent Abstracts of Japan**

;PUBLICATION NUMBER

58189950

-PUBLICATION DATE

05-11-83

APPLICATION DATE

30-04-82

**APPLICATION NUMBER** 

57071450

APPLICANT: HITACHI SEIKI KK;

INVENTOR :


KATAGIRI SHINJIRO:

INT.CL.

H01J 37/22 H01J 37/26

TITLE

**ELECTRON MICROSCOPE** 



ABSTRACT :

PURPOSE: To escape from the radiation of X-rays produced when an electron collides with an object as well as to prevent a drop in an S/N ratio of detector output used by deterioration in a condenser, by setting up the condenser at a position away from the axis of an electron beam.

CONSTITUTION: An electron beam 1 transmitted through an unillustrated sample is projected on an optical conversion screen 4 by a projection lens 2 and converted into light. This converted light is reflected in a rectangular direction by a reflector mirro 5 installed in the axis of the electron beam 1 at the rear step of the screen 4 while this reflected light is focused on a camera tube 7 by a condenser 6 installed in a position some distant from the axis of the electron beam 1. When both the electron beam 1 transmitted through the sample and scattering electrons collide with an object existing in a passage of the electron beam 1 or the vicinity, X-rays are generated. However, since the condenser 6 is situated in a position away from the axis of the electron beam 1, it escapes from X-ray radiation. Consequently, deterioration in the condenser 6 from which a drop in the optical penetrability of the condenser 6 may occur is prevented and thereby an S/N ratio of detector output will not come down at all.

COPYRIGHT: (C) JPO